




SWIFTCO 5.50M 2000KG BOAT TRAILER DATA SHEET



SIZES AND WEIGHTS

- ✓ Bow Eye to Transom From: 4.50m to 5.150m
- ✓ Bow to Transom boat length: 5.10m to 5.70m
- ✓ Boat-Motor-Trailer Weight (BMT): 2000Kg
- ✓ Trailer Weight: 390Kg
- ✓ Trailer OA Length: 6.40m
- ✓ Trailer OA Width: 2.350m
- ✓ Distance Between Guards: 1.850m
- ✓ Chassis Main Beam: 152mm Aluminium I Beam T6 400MPA

SPECIFICATIONS

- ✓ Axles: 2 x Ford (3000Kg) Load Share
- ✓ Axle Type 50mm:
- ✓ Wheel Size: 14 Inch Galvanised
- ✓ Boat Support: Keel Ladder & Wobble Rollers = 24
- ✓ Chassis Assembly: Sandwich Plated
- ✓ Stud Pattern: Ford
- ✓ Lighting: LED Submersible Type
- ✓ Winch Type: 950Kg Webbing/strap
- ✓ Brake Type: Mechanical Brake System
- ✓ Calliper Mechanical
- ✓ Rotor Type: 10"

Swiftco have been manufacturing high quality trailers **Since 1975.**

ROVER APPROVED (Federal Road vehicle Standards legislation) manufactured to strict **Australian Standards.**

INDUSTRY LEADING 6 YEAR FRAME WARRANTY.

... so you can ALWAYS trust a Swiftco.

The boat trailer comes standard with:

- ✓ 152mm T6 Structural Aluminum I Beam (400MPA)
- ✓ Frame tested and rated to over 35000Kg
- ✓ 6 Year Frame Warranty
- ✓ 5 Year Light Warranty
- ✓ New 11 Tank Marine Powdercoat brackets (Eliminating Electrolysis)
- ✓ Comes Standard with Keel Ladder roller System
- ✓ Alloy Wheels as Upgrade
- ✓ Heavy Duty Load Share Galvanised Suspension
- ✓ Comes Standard with Mechanical brake system
- ✓ Comes Standard with 10" Disc Rotors
- ✓ Choice of Jockey wheel or Removable Jockey Stand